



## MATERIAL SAFETY DATA SHEET

### SUPERIOR No. 100-20

DATE REVISED: November 11, 2003

**Product Name:** Superior No. 100-20

**Manufacturer:** Superior Flux & Mfg. Co. 6615 Parkland Blvd. Cleveland, OH 44139

**Emergency Phone Number:** 1-800-424-9300 (CHEMTREC)

**Other Information Calls:** (440) 349-3000

**To the Purchaser:** This MSDS contains important environmental, health, and toxicology information for your employees who have ordered this product. Please be sure this information is given to them. If you resell this product, a copy of the MSDS should be given to the buyer.

**H.M.I.S. INFORMATION: HEALTH = 2      FLAMMABILITY = 3      REACTIVITY = 0**

### SECTION I - IDENTIFICATION

**Common Name:** Superior No. 100-20

**Chemical Family:** Rosin Soldering Flux

**CAS Number:** NA

**Chemical Name:** NA

**Formula:** See Below

### SECTION II - COMPOSITION INFORMATION

<u>Components</u>	<u>CAS Number</u>	<u>%</u>	<u>OSHA PEL</u>
Isopropanol	67-63-0	50-70	400 PPM
Gum Rosin	8050-09-07	18-22	NA
Mineral Spirits	8032-32-4	7-12	500PPM
Dimethylamine-HCl	506-59-2	1-3	10PPM

Unlisted percentages are non-hazardous stabilizers, activators, and water. None of the materials in this product are listed in NTP, IARC, or OSHA as carcinogens.

### SECTION III - HEALTH HAZARDS

#### EMERGENCY AND FIRST AID PROCEDURES

**Eyes:** Flush with Water for 15 Minutes. Call a Physician.

**Skin:** Wash Thoroughly with Soap and Water.

**Inhalation:** Remove to Fresh Air or Administer Oxygen. Call Physician.

**Ingestion:** If Patient is Fully Conscious, Give Large Amounts of Water and Induce Vomiting. Obtain Medical Attention Immediately.

**Primary Routes of Entry:** Fume Inhalation, Ingestion, Skin, and Eyes.

**Symptoms of Overexposure:** Dizziness, Blurred Vision, Headache, Irritation of Mucous Membranes, Nausea, and Loss of Consciousness. Can Be Fatal if Swallowed.

**Medical Conditions Generally Aggravated by Overexposure:** Skin Conditions, Kidney or Liver Diseases, or Central Nervous System.

**Chemical Listed as a Carcinogen or Potential Carcinogen:** None

**OSHA Permissible Exposure Limit (PEL):** 10 PPM

**ACGIH Threshold Limit Value (TLV):** 10 PPM

*Superior manufactures quality fluxes. Our business is solving problems.*



## SECTION IV - FIRE AND EXPLOSION HAZARD DATA

**Flash Point:** 53°F

**Flammable Limits:** Lower-0.9 Upper-7

**Extinguishing Media:** Dry Chemical, CO<sub>2</sub>, and Alcohol Resistant Foam

**Auto Ignition Temperature:** 398.9°C/750°F

**Special Fire Fighting Procedures:** NIOSH Approved Self-Contained Breathing Apparatus

**Unusual Fire and Explosion Hazards:** Flammable, Do Not Mix with Strong Oxidizing or Dehydrating Agents. Do Not Store in Presence of Oxidizing Agents

## SECTION V - ACCIDENTAL RELEASE MEASURES

**Steps to be Taken in Case Material is Spilled:** Absorb with Sawdust and Remove in Accordance to EPA Regulations.

## SECTION VI - HANDLING AND STORAGE

**Storage Requirements:** Store in Plastic Containers in Cool Area. Do Not Store in Glass Containers.

**Handling Precautions:** Safe Precautionary Practices.

**Other Precautions:** Keep Away From Electrical Sparks, Heat, Open Flame or Oxidizing Agents.

## SECTION VII - CONTROL MEASURES

**Respiratory Protection (TYPE):** NIOSH Approved Respirator.

**Ventilation:** Yes

**Mechanical (General):** Explosion Proof

**Local Exhaust:** Yes

**Eye Protection:** Safety Glasses

**Protective Gloves:** Recommended, NIOSH Approved

**Other Protective Clothing or Equipment:** Rubber Apron is Recommended

## SECTION VIII - PHYSICAL AND CHEMICAL CHARACTERISTICS

**Boiling Point:** 180°F

**Specific Gravity (Water = 1):** 0.85

**Vapor Pressure (mm Hg):** 31@68°F

**Percent Volatile by Volume:** 58.0%

**Vapor Density (Air = 1):** 2.07

**Evaporation Rate (Butyl Acetate = 1):** 2.2

**Melting Point:** NA

**Solubility in Water:** Insoluble

**Reactivity in Water:** None

**Appearance and Odor:** Brown Liquid, Alcohol Odor

## SECTION IX - STABILITY AND REACTIVITY

**Stability:** Product is Stable

**(Conditions to Avoid):** Avoid Heat, Sparks, and Open Flames

**Incompatibility:** Strong Oxidizers, Alkaline Compounds

**Hazardous Decomposition Products:** Aliphatic Aldehydes.

**Hazardous Polymerization:** NA

**(Conditions to Avoid):** NA

## SECTION X - TRANSPORTATION AND DISPOSAL CONSIDERATIONS

**D.O.T. Proper Shipping Name:** Flammable Liquid, NOS (Contains Isopropanol and Mineral Spirits)

**Hazard Class:** 3

**Identification Number:** UN1993

**Packing Group:** II

**Type D.O.T Label Required Information:** Flammable Liquid

**Waste Disposal Method:** Dispose of in Accordance with State and Local EPA Regulations

**Disclaimer:** Judgments as to the suitability of information herein or the purchaser's purposes are necessarily the purchaser's responsibility. Reasonable care has been taken in the preparation of this material, but there are NO WARRANTIES, NO REPRESENTATIONS, AND NO RESPONSIBILITY AS TO THE ACCURACY OR THE SUITABILITY OF THIS INFORMATION FOR ANY PURCHASER'S USE OR FOR ANY CONSEQUENCE TO USE.

MSDS: Superior No. 100-20 p2/2

The information contained herein is based on data considered to be accurate and is intended for use by persons having technical skills at their own discretion and risk. Since conditions of use are outside of Superior Flux & Mfg. Co.'s control, we cannot assume liability for results obtained or damage incurred due to misuse, nor can we assume customer liability.

**Superior manufactures quality fluxes. Our business is solving problems.**



**Superior Flux  
& Mfg. Co.**

6615 Parkland Blvd. • Cleveland, OH 44139 • Phone: 440-349-3000 • Fax: 440-349-3003  
www.superiorflux.com • e-mail: info@superiorflux.com