



## MATERIAL SAFETY DATA SHEET SUPERIOR 3000 NO-CLEAN TACKY FLUX

DATE REVISED: April 10, 2003



**Product Name:** Superior 3000 No-Clean Tacky Flux  
**Manufacturer:** Superior Flux & Mfg. Co. 6615 Parkland Blvd. Cleveland, OH 44139  
**Emergency Phone Number:** 1-800-424-9300 (CHEMTREC)  
**Other Information Calls:** (440) 349-3000

To the Purchaser: This MSDS contains important environmental, health, and toxicology information for your employees who have ordered this product. Please be sure this information is given to them. If you resell this product, a copy of the MSDS should be given to the buyer.

**H.M.I.S. INFORMATION: HEALTH = 1      FLAMMABILITY = 1      REACTIVITY = 1**

### SECTION I - IDENTIFICATION

**Common Name:** Superior 3000 No-Clean Tacky Flux      **Chemical Family:** Tacky Flux  
**CAS Number:** NA      **Chemical Name:** NA  
**Formula:** See Below

### SECTION II - COMPOSITION INFORMATION

Components	CAS Number	OSHA PEL	ACGIH TLV	Other Recommended Limit
--	--	--	--	--

Unlisted percentages are non-hazardous stabilizers, activators, and water. None of the materials in this product are listed in NTP, IARC, or OSHA as carcinogens.

### SECTION III - HEALTH HAZARDS

#### EMERGENCY AND FIRST AID PROCEDURES

**Eyes:** Flush with Water for 10 Minutes. Call a Physician.  
**Skin:** Wash Thoroughly with Water.  
**Inhalation:** Remove to Fresh Air or Administer Oxygen. Call Physician.  
**Ingestion:** Get Medical Attention.  
**Primary Routes of Entry:** Fume Inhalation, Ingestion, Skin, and Eyes.  
**Symptoms of Overexposure:** No Specific Information Available.  
**Medical Conditions Generally Aggravated by Overexposure:** None Presently Known.  
**Chemical Listed as a Carcinogen or Potential Carcinogen:** None Known  
**OSHA Permissible Exposure Limit (PEL):** NA  
**ACGIH Threshold Limit Value (TLV):** NA

### SECTION IV - FIRE AND EXPLOSION HAZARD DATA

**Flash Point:** Core > 140°C      **Metal:** NA  
**Flammable Limits:** NA  
**Extinguishing Media:** Special Mixtures of Dry Chemicals Suitable for Metal Fires Such as Dry Sand, Dolomite, Graphite, Salt, Soda Ash. **Do Not Apply Water to Burning or Melted Metal.** Water Can be Used to Cool Containers When No Contact with Metal Will Occur.  
**Auto Ignition Temperature:** NA  
**Special Fire Fighting Procedures:** Avoid Breathing Fumes, Smoke From Fire, And Use Self-Contained Breathing Gear.  
**Unusual Fire and Explosion Hazards:** None Known.

*Superior manufactures quality fluxes. Our business is solving problems.*



## SECTION V - ACCIDENTAL RELEASE MEASURES

**Steps to be Taken in Case Material is Spilled:** Protect Skin and Eyes by Wearing Safety Glasses and Gloves. Ventilate the Area. Restrict and Collect Spilled Materials.

## SECTION VI - HANDLING AND STORAGE

**Storage Requirements:** Store in Low Temperature and Low Humidity Area.

**Handling Precautions:** Users Should Wear Protective Gloves and Glasses When Handling Solder Paste. Soldering Should be Conducted in Good Ventilation Environment.

**Other Precautions:** Keep the Tin, Silver, and Lead Fume Levels Below the OSHA Permissible Exposure Limit.

## SECTION VII - CONTROL MEASURES

**Respiratory Protection (TYPE):** NIOSH Approved.

**Ventilation:** Yes

**Mechanical (General):** Optional

**Local Exhaust:** Yes

**Eye Protection:** Safety Glasses

**Protective Gloves:** Rubber Gloves

**Other Protective Clothing or Equipment:** Laboratory or Worker Coat.

**Work/Hygienic Practices:** Wash Hands After Handling the Product, Wear Safety Glasses During Handling.

## SECTION VIII - PHYSICAL AND CHEMICAL CHARACTERISTICS

**Boiling Point:** NA

**Specific Gravity (Water = 1):** 4.0-5.5

**Vapor Pressure (mm Hg):** NA

**Percent Volatile by Volume:** NA

**Vapor Density (Air = 1):** NA

**Evaporation Rate (Butyl Acetate = 1):** NA

**Melting Point:** 183°C

**Solubility in Water:** Partial

**Reactivity in Water:** None

**Appearance and Odor:** Pasty and Mild Solvent Odor

## SECTION IX - STABILITY AND REACTIVITY

**Stability:** Product is Stable      **(Conditions to Avoid):** Contact With Strong Acids and Alkali.

**Incompatibility:** Strong Acids and Alkali.

**Hazardous Decomposition Products:** Not Determined.

**Hazardous Polymerization:** Not Determined.      **(Conditions to Avoid):** Not Determined.

## SECTION X - TRANSPORTATION AND DISPOSAL CONSIDERATIONS

**D.O.T. Proper Shipping Name:** Non-Hazardous

**Hazard Class:** NA

**Identification Number:** NA

**Packing Group:** NA

**Type D.O.T Label Required Information:** NA

**Waste Disposal Method:** Incinerate or Dispose of per Federal, State, or Local Regulations.

**Disclaimer:** Judgments as to the suitability of information herein or the purchaser's purposes are necessarily the purchaser's responsibility. Reasonable care has been taken in the preparation of this material, but there are NO WARRANTIES, NO REPRESENTATIONS, AND NO RESPONSIBILITY AS TO THE ACCURACY OR THE SUITABILITY OF THIS INFORMATION FOR ANY PURCHASER'S USE OR FOR ANY CONSEQUENCE TO USE.

MSDS: Superior 3000 No-Clean Tacky Flux p2/2

The information contained herein is based on data considered to be accurate and is intended for use by persons having technical skills at their own discretion and risk. Since conditions of use are outside of Superior Flux & Mfg. Co.'s control, we cannot assume liability for results obtained or damage incurred due to misuse, nor can we assume customer liability.

**Superior manufactures quality fluxes. Our business is solving problems.**



**Superior Flux  
& Mfg. Co.**

6615 Parkland Blvd. • Cleveland, OH 44139 • Phone: 440-349-3000 • Fax: 440-349-3003  
www.superiorflux.com • e-mail: info@superiorflux.com