



MATERIAL SAFETY DATA SHEET

SUPERIOR No. 555C

DATE REVISED: November 20, 2003



Product Name: Superior No. 555C

Manufacturer: Superior Flux & Mfg. Co. 6615 Parkland Blvd. Cleveland, OH 44139

Emergency Phone Number: 1-800-424-9300 (CHEMTREC)

Other Information Calls: (440) 349-3000

To the Purchaser: This MSDS contains important environmental, health, and toxicology information for your employees who have ordered this product. Please be sure this information is given to them. If you resell this product, a copy of the MSDS should be given to the buyer.

H.M.I.S. Information:	HEALTH = 2	FLAMMABILITY = 0	REACTIVITY = 0
------------------------------	-------------------	-------------------------	-----------------------

SECTION I - IDENTITY

Common Name: Superior No. 555C

Chemical Family: Inorganic Acid, Battery Flux

CAS Number: NA

Chemical Name: NA

Formula: See Below

SECTION II - COMPOSITION INFORMATION

<u>Components</u>	<u>CAS Number</u>	<u>%</u>	<u>OSHA PEL</u>
Hydrobromic Acid	10035-10-6	20-60	3PPM
Monoethanolamine	141-43-5	5-20	3PPM
Phosphoric Acid	7665-38-2	5-20	NA

Unlisted percentages are non-hazardous stabilizers, activators, and water. None of the materials in this product are listed in NTP, IARC, or OSHA as carcinogens.

SECTION III - HEALTH HAZARDS

EMERGENCY AND FIRST AID PROCEDURES

Inhalation: Remove Victim to Fresh Air

Ingestion: Drink Water or Milk. Call a Physician

Eyes: Flush with Water for 10 Minutes. Call a Physician.

Skin: Wash Thoroughly With Water.

Primary Routes of Entry into Body: Fume Inhalation, Ingestion, Skin, and Eyes.

Symptoms of Overexposure: Irritation of Eye, Skin, Mucous Membranes, and Acid Stomach if Ingested.

Medical Conditions Generally Aggravated by Exposure: None Presently Known

Chemicals Listed as Carcinogen or Potential Carcinogen: None

OSHA Permissible Exposure Limit (PEL): 3PPM

ACCGIH Threshold Limit Value (TLV): 5PPM

Superior manufactures quality fluxes. Our business is solving problems.



Superior Flux & Mfg. Co.

6615 Parkland Blvd. • Cleveland, OH 44139 • Phone: 440-349-3000 • Fax: 440-349-3003
www.superiorflux.com • e-mail: info@superiorflux.com

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flash Point: NA
Extinguishing Media: CO₂, Dry Chemical
Unusual Fire and Explosion Hazards: Will Release Small Amounts of HBr.
Special Fire Fighting Procedures: None

Flammable Limits in Air % By Volume: NA
Auto Ignition Temperature: None

SECTION V - ACCIDENTAL RELEASE MEASURES

Steps to be Taken in Case Material is Spilled: First Neutralize with Soda Ash or Sodium Bicarbonate, Dilute with Water and Dispose in Accordance with EPA Regulations and Wash with Plenty of Water.

SECTION VI - HANDLING AND STORAGE

Storage Requirements: Plastic Containers in a Cool Dry Place Away From Heat.
Handling Requirements: Safe Precautionary Use to Prevent Spills and Exposure to Skin or Fumes.
Other Precautions: None

SECTION VII - CONTROL MEASURES

Respiratory Protection (TYPE): NIOSH Approved Respirator.
Mechanical (General): Yes
Eye Protection: Safety Glasses/Goggles
Protective Gloves: Recommended, NIOSH Approved
Other Protective Clothing or Equipment: Optional to User's Preference.

Ventilation: Yes
Local Exhaust: Yes

SECTION VIII - PHYSICAL AND CHEMICAL CHARACTERISTICS

Boiling Point: ~104°C/220°F
Vapor Pressure (mmHg): Nil
Vapor Density (Air = 1): NA
Melting Point: ~0°C/32°F
Reactivity in Water: None

Specific Gravity (Water = 1): 1.252
Percent Volatile By Volume: 40%
Evaporation Rate (Butyl acetate = 1): NA
Solubility in Water: Unlimited
Appearance and Odor: Clear, Odorless Liquid

SECTION IX - STABILITY AND REACTIVITY

Stability: Product is Stable
Hazardous Polymerization: None
Incompatibility: Oxidizing Agents and Metals.
Hazardous Decomposition Products: Hydrobromides, P₂O₅, Nitrogen Products, CO, CO₂

Conditions to Avoid: None
Conditions to Avoid: Extreme Heat

SECTION X - TRANSPORTATION AND DISPOSAL CONSIDERATIONS

D.O.T. Proper Shipping Name: Corrosive Liquid, Acidic, Inorganic N.O.S. (Contains Hydrobromic Acid, Phosphoric Acid).
Hazard Class: 8
Identification Number: UN3264
Packing Group: III
Type D.O.T Label Required Information: Corrosive
Waste Disposal Method: Dispose in Accordance with EPA Regulations.

Judgments as to the suitability of information herein or the purchaser's purposes are necessarily the purchaser's responsibility. Reasonable care has been taken in the preparation of this material, but there are NO WARRANTIES, NO REPRESENTATIONS, AND NO RESPONSIBILITY AS TO THE ACCURACY OR THE SUITABILITY OF THIS INFORMATION FOR ANY PURCHASER'S USE OR FOR ANY CONSEQUENCE TO USE.

MSDS - Superior No. 555C p 2/2

The information contained herein is based on data considered to be accurate and is intended for use by persons having technical skills at their own discretion and risk. Since conditions of use are outside of Superior Flux & Mfg. Co.'s control, we cannot assume liability for results obtained or damage incurred due to misuse, nor can we assume customer liability.

Superior manufactures quality fluxes. Our business is solving problems.



**Superior Flux
& Mfg. Co.**

6615 Parkland Blvd. • Cleveland, OH 44139 • Phone: 440-349-3000 • Fax: 440-349-3003
www.superiorflux.com • e-mail: info@superiorflux.com